

## LISTING OF CLAIMS

This Listing of Claims will replace all prior versions and Listings of Claims in the application:

1. (Presently Amended) A method, comprising:  
receiving input indicating that a first stylus is located proximate to a digitizer in a hovering orientation; and  
providing focus to a first control element corresponding to a location of the first stylus in the hovering orientation.
2. (Original) A method according to claim 1, further comprising:  
accepting input in an area of the digitizer representing the first control element.
3. (Original) A method according to claim 2, wherein the input includes electronic ink.
4. (Original) A method according to claim 1, further comprising:  
moving the first stylus away from the digitizer without contacting a surface of the digitizer such that the input indicating first stylus proximity is no longer received; and  
withdrawing focus from the first control element.
5. (Presently Amended) A method according to claim 1, wherein prior to providing focus, the method further includes:  
determining a location of the first stylus in the hovering orientation with respect to representations of plural control elements of a user interface on a screen.
6. (Original) A method according to claim 1, wherein providing focus includes rendering an enlarged view of at least a portion of a representation of the first control element.
7. (Original) A method according to claim 1, wherein providing focus includes providing an enlarged area for accepting input directed to the first control element.
8. (Presently Amended) A method according to claim 1, further comprising:

maintaining a mouse focus separate from the focus corresponding to the first stylus location in the hovering orientation.

9. (Presently Amended) A method according to claim 1, further comprising:  
maintaining a keyboard focus separate from the focus corresponding to the first stylus location in the hovering orientation.

10. (Original) A method according to claim 1, further comprising:  
preparing the first control element to receive input.

11. (Original) A method according to claim 10, wherein the preparing includes increasing a polling frequency in an area of the digitizer corresponding to the first control element.

12. (Presently Amended) A method according to claim 1, further comprising:  
receiving a second input indicating that a second stylus is located proximate to the digitizer in a hovering orientation.

13. (Presently Amended) A method according to claim 12, further comprising:  
providing focus to a second control element corresponding to a location of the second stylus in the hovering orientation.

14. (Original) A method according to claim 13, wherein focus to the second control element is provided concurrent with focus to the first control element.

15. (Original) A method according to claim 1, further comprising:  
moving the first stylus from a first area corresponding to the first control element to a second area corresponding to a second control element; and  
changing focus from the first control element to the second control element.

16. (Original) A method according to claim 15, wherein the first stylus does not contact a surface of the digitizer prior to moving from the first area to the second area.

17. (Original) A method according to claim 16, wherein the first stylus contacts a surface of the digitizer prior to moving from the first area to the second area.

18. (Original) A method according to claim 1, further comprising providing at least one of a visual or audio indicator when focus is provided.

19. (Presently Amended) A method, comprising:  
determining whether a first stylus is located proximate to a surface of a digitizer in a hovering orientation; and  
providing focus to a first control element corresponding to a location of the first stylus in response to: (a) a determination that the first stylus is located proximate to the digitizer in the hovering orientation, or (b) contact between the first stylus and the surface of the digitizer.

20. (Original) A method according to claim 19, further comprising:  
determining that the first stylus is located proximate to the digitizer surface and providing the focus in response to this determination.

21. (Original) A method according to claim 19, further comprising:  
sensing contact between the first stylus and the surface of the digitizer and providing the focus in response to the sensing.

22. (Original) A method according to claim 19, further comprising:  
accepting electronic ink or other input in an area of the digitizer representing the first control element.

23. (Original) A method according to claim 19, wherein providing focus includes providing an enlarged area for accepting input directed to the first control element.

24. (Original) A method according to claim 19, further comprising:  
preparing the first control element to receive input.

25. (Original) A method according to claim 24, wherein the preparing includes increasing a polling frequency in an area of the digitizer corresponding to the first control element.

26. (Presently Amended) A method according to claim 19, further comprising:  
determining whether a second stylus is located proximate to the surface of the digitizer in a hovering orientation.

27. (Presently Amended) A method according to claim 26, further comprising:  
providing focus to a second control element when a location of the second stylus corresponds to an area of the digitizer representing the second control element in response to: (a) a determination that the second stylus is located proximate to the digitizer in the hovering orientation, or (b) contact between the second stylus and the surface of the digitizer.

28. (Original) A method according to claim 27, wherein focus to the second control element is provided concurrent with focus to the first control element.

29. (Original) A method according to claim 19, further comprising:  
moving the first stylus from a first area corresponding to the first control element to a second area corresponding to a second control element; and  
changing focus from the first control element to the second control element.

30. (Original) A method according to claim 19, further comprising providing at least one of a visual or audio indicator when focus is provided.

31. (Presently Amended) A system, comprising:  
an input device adapted to generate an input indicating that a first stylus is located proximate to a digitizer in a hovering orientation; and  
a processor programmed and adapted to provide focus to a first control element corresponding to a location of the first stylus in the hovering orientation.

32. (Original) A system according to claim 31, wherein the input device is further adapted to accept input in an area of the digitizer representing the first control element.

33. (Original) A system according to claim 32, wherein the input includes electronic ink input.

34. (Original) A system according to claim 31, wherein the processor is further programmed and adapted to withdraw focus from the first control element when the first stylus is moved away from the digitizer without contacting a surface of the digitizer to an extent such that the input indicating first stylus proximity is no longer received.

35. (Presently Amended) A system according to claim 31, wherein the processor is further programmed and adapted to determine a location of the first stylus in the hovering orientation with respect to representations of plural control elements of a user interface on a screen prior to providing the focus.

36. (Original) A system according to claim 31, wherein the processor is further programmed and adapted to provide an enlarged area for accepting input directed to the first control element in response to the first control element receiving focus.

37. (Presently Amended) A system according to claim 31, wherein the processor is further programmed and adapted to maintain a mouse focus separate from the focus corresponding to the first stylus location in the hovering orientation.

38. (Presently Amended) A system according to claim 31, wherein the processor is further programmed and adapted to maintain a keyboard focus separate from the focus corresponding to the first stylus location in the hovering orientation.

39. (Original) A system according to claim 31, wherein the processor is further programmed and adapted to prepare the first control element to receive input in response to receiving the focus.

40. (Original) A system according to claim 39, wherein the processor is programmed and adapted to prepare the first control element to receive input by increasing a polling frequency in an area of the digitizer corresponding to the first control element.

41. (Presently Amended) A system according to claim 31, wherein the input device is further adapted to generate a second input indicating that a second stylus is located proximate the digitizer in a hovering orientation.

42. (Presently Amended) A system according to claim 41, wherein the processor is further programmed and adapted to provide focus to a second control element corresponding to a location of the second stylus in the hovering orientation in response to the second input.

43. (Original) A system according to claim 42, wherein focus to the second control element is provided concurrent with focus to the first control element.

44. (Original) A system according to claim 31, wherein the processor is further programmed and adapted to change focus from the first control element to a second control element when the first stylus is moved from a first area corresponding to the first control element to a second area corresponding to the second control element.

45. (Original) A system according to claim 31, wherein the processor is further programmed and adapted to provide at least one of a visual or audio indicator when focus is provided.

46. (Presently Amended) A system, comprising:  
an input device adapted to generate an input indicating when a first stylus is located proximate a surface of a digitizer in a hovering orientation; and  
a processor programmed and adapted to provide focus to a first control element corresponding to a location of the first stylus in response to: (a) a determination that the first stylus is located proximate to the digitizer in the hovering orientation, or (b) contact between the first stylus and the surface of the digitizer.

47. (Original) A system according to claim 46, wherein the input device is further adapted to accept electronic ink or other input in an area of the digitizer representing the first control element.

48. (Original) A system according to claim 46, wherein the processor is further programmed and adapted to provide an enlarged area for accepting input directed to the first control element in response to the first control element receiving focus.

49. (Original) A system according to claim 46, wherein the processor is further programmed and adapted to prepare the first control element to receive input in response to receiving the focus.

50. (Original) A system according to claim 49, wherein the processor is programmed and adapted to prepare the first control element to receive the input by increasing a polling frequency in an area of the digitizer corresponding to the first control element.

51. (Presently Amended) A system according to claim 46, wherein the input device is further adapted to generate a second input indicating that a second stylus is located proximate the digitizer in a hovering orientation.

52. (Presently Amended) A system according to claim 51, wherein the processor is further programmed and adapted to provide focus to a second control element when a location of the second stylus corresponds to an area of the digitizer representing the second control element in response to: (a) a determination that the second stylus is located proximate to the digitizer in the hovering orientation, or (b) contact between the second stylus and the surface of the digitizer.

53. (Original) A system according to claim 52, wherein focus to the second control element is provided concurrent with focus to the first control element.

54. (Original) A system according to claim 46, wherein the processor is further programmed and adapted to change focus from the first control element to a second control element when the first stylus is moved from a first area corresponding to the first control element to a second area corresponding to the second control element.

55. (Original) A system according to claim 46, wherein the processor is further programmed and adapted to provide at least one of a visual or audio indicator when focus is provided.

56. (Presently Amended) A computer-readable medium including computer-executable instructions stored thereon for performing a method comprising:

receiving input indicating that a first stylus is located proximate to a digitizer in a hovering orientation; and

providing focus to a first control element corresponding to a location of the first stylus in the hovering orientation.

57. (Original) A computer-readable medium according to claim 56, wherein the method further includes:

accepting electronic ink or other input in an area of the digitizer representing the first control element.

58. (Original) A computer-readable medium according to claim 56, wherein the method further includes:

withdrawing focus from the first control element when the first stylus is moved away from the digitizer without contacting a surface of the digitizer such that the input indicating first stylus proximity is no longer received.

59. (Original) A computer-readable medium according to claim 56, wherein the method further includes:

providing an enlarged area for accepting input directed to the first control element in response to receiving the focus.

60. (Original) A computer-readable medium according to claim 56, wherein the method further includes:

increasing a polling frequency in an area of the digitizer corresponding to the first control element.

61. (Presently Amended) A computer-readable medium according to claim 56, wherein the method further includes:

receiving a second input indicating that a second stylus is located proximate the digitizer in a hovering orientation.

62. (Presently Amended) A computer-readable medium according to claim 61, wherein the method further includes:

providing focus to a second control element corresponding to a location of the second stylus in the hovering orientation in response to the second input.

63. (Original) A computer-readable medium according to claim 56, wherein the method further includes:

changing focus from the first control element to the second control element when the first stylus is moved from a first area corresponding to the first control element to a second area corresponding to a second control element.

64. (Original) A computer-readable medium according to claim 56, wherein the method further includes providing at least one of a visual or audio indicator when focus is provided.



65. (Presently Amended) A computer-readable medium including computer-executable instructions stored thereon for performing a method comprising:

determining whether a first stylus is located proximate to a surface of a digitizer in a hovering orientation; and

providing focus to a first control element corresponding to a location of the first stylus in response to: (a) a determination that the first stylus is located proximate to the digitizer in the hovering orientation, or (b) contact between the first stylus and the surface of the digitizer.

66. (Original) A computer-readable medium according to claim 65, wherein the method further includes:

accepting electronic ink or other input in an area of the digitizer representing the first control element.

67. (Original) A computer-readable medium according to claim 65, wherein the method further includes:

providing an enlarged area for accepting input directed to the first control element in response to receiving the focus.

68. (Original) A computer-readable medium according to claim 65, wherein the method further includes:

increasing a polling frequency in an area of the digitizer corresponding to the first control element.

69. (Presently Amended) A computer-readable medium according to claim 65, wherein the method further includes:

determining whether a second stylus is located proximate to the surface of the digitizer in a hovering orientation.

70. (Presently Amended) A computer-readable medium according to claim 69, wherein the method further includes:

providing focus to a second control element when a location of the second stylus corresponds to an area of the digitizer representing the second control element in response to: (a) a determination

that the second stylus is located proximate to the digitizer in the hovering orientation, or (b) contact between the second stylus and the surface of the digitizer.

71. (Original) A computer-readable medium according to claim 65, wherein the method further includes:

changing focus from the first control element to a second control element when the first stylus is moved from a first area corresponding to the first control element to a second area corresponding to the second control element.

72. (Original) A computer-readable medium according to claim 65, wherein the method further includes providing at least one of a visual or audio indicator when focus is provided.